

ATEAP-PVL10

10,000 lb. Capacity Overhead 2-Post Lift







SPECIFICATIONS:

- Capacity: 10,000 LB.
- Overall Height: 135 7/8" (11' 3 7/8") or 139 7/8" (11' 7 7/8")
- Overall Height for Cylinder Extension: 148" (12' 4")
- Overall Floor Width: 139" Asymmetric / 137 ½" Symmetric
- Outside Columns: 130" Asymmetric / 129 1/4" Symmetric
- Inside Column: 107 3/4" Asymmetric / 112 1/2" Symmetric
- Drive Thru: 91" Asymmetric / 99 ½" Symmetric
- Max Lift Height w/o Adapters: 72 ½"
- Max Lift Height w/ Adapters: 81 ½"
- Minimum Arm Height: 4"
- Column Size: 7" x 10 1/4"
- Base Of Lift: 15" x 18"
- Adapter Heights: 4 Each 3", 6"
- Arm Hole/Adapter Peg Size: 2"
- Shipping Weight: 1,850 LBS.

FEATURES:

- ALI Certified Lift
- Special Double "S" Bend Column Design
- Can be installed Symmetrically OR Asymmetrically
- Padded Carriages
- 3-Stage Front Arms & 2-Stage Rear Arms
- Single-Point Lock Release
- Powder Coat Finish
- Includes Double Screw-up Adapters
- Free 8 Piece Truck Adapter Set
- Mounting Hardware Included
- 30 Amp Breaker Required
- Standard with Premium ALLY Power Unit
- 5 year Structural Warranty
- 2 year Hydraulic Warranty
- 2 year Power Unit Warranty

The Atlas® Platinum PVL10 is a 2-post 10,000 lb. capacity ALI Certified commercial grade lift designed with the professional shop in mind. The Platinum PVL10 was engineered and built with the reliability offered by the Double S column design and can be installed with the columns positioned symmetrically or asymmetrically.

The Atlas® Platinum PVL10 features three (3) stage telescoping front arms, double screw rubber/metal adapters with truck height extensions, protective rubber pads mounted to the carriage, and rubber column guards.

This product also features an ALLY Hydraulic AL2850 Power Unit. This premium power unit is certified by MET Laboratories Inc. for electrical compliance in the United States and Canada.

Atlas Automotive Equipment experts are standing by with helpful sales tips!

888-327-0222

AtlasAutoEquipment.ca